

EDK120S15R1L

ev™ Silicon Carbide Schottky Diode 1200V, 15A

Features

- Zero Reverse Recovery Current
- Low Forward Voltage
- High Surge Current Capability
- Independent of Temperature Switching Behavior
- Positive Temperature Coefficient
- Max Junction Temperature 175 °C
- Pb-free, Halogen Free, and RoHS Compliant



Benefits

- Higher Efficiency
- Ease of Paralleling
- Increased Power Density
- Reduced Cooling Requirements

Applications

- Solar Inverters
- Power Factor Correction
- Industrial Power Supply
- EV Charging Station

V_{RRM}	$I_F, T_C=25^\circ C$	$T_{J, Max}$	Q_C, Typ
1200V	15A	175°C	92nC



Ordering Information

Part Number	Package	Shipping	Quantity
EDK120S15R1L	TO-220-2L	Tube	50 units

Absolute Maximum Ratings ($T_C=25^\circ C$, unless otherwise specified)

Symbol	Parameter	Value	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Forward Current	$T_C=157^\circ C$ 15	A
$I_{F,SM}$	Non-Repetitive Forward Surge Current	$T_C=25^\circ C, t_p=10ms$	110
		$T_C=150^\circ C, t_p=10ms$	90
$I_{F,Max}$	Non-Repetitive Peak Forward Current	$T_C=25^\circ C, t_p=10\mu s$	850
		$T_C=150^\circ C, t_p=10\mu s$	725
I^2dt value	$\int I^2t$	$T_C=25^\circ C, t_p=10ms$	60.5
		$T_C=150^\circ C, t_p=10ms$	40.5
P_{tot}	Power Dissipation	$T_C=25^\circ C$ 294	W
T_J, T_{STG}	Operating and Storage Temperature Range	-55 to 175	°C







■ Thermal Characteristics

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Maximum Thermal Resistance, Junction to Case	0.51	°C/W

■ Electrical Characteristics (T_C=25°C, unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_F	Forward Voltage	$I_F=15A, T_J=25^\circ C$		1.39	1.70	V
		$I_F=15A, T_J=175^\circ C$		1.80		
I_R	Reverse Current	$V_R=1200V, T_J=25^\circ C$			100	μA
		$V_R=1200V, T_J=175^\circ C$			300	
Q_C	Total Capacitive Charge	$V_R=800V, T_J=25^\circ C$		92		nC
C	Total Capacitance	$V_R=1V, f=100kHz$		1010		pF
		$V_R=800V, f=100kHz$		65		
E_C	Capacitance Stored Energy	$V_R=800V$		26		μJ

■ **Typical Characteristics** ($T_J=25^\circ\text{C}$ unless otherwise noted)



■ Typical Characteristics

Figure 7. Capacitive Characteristics






Figure 8. Transient Thermal Response Curve



Package Outlines

TO-220-2L



SYMBOL	MIN	NOM	MAX
A	4.30	4.50	4.70
A1	1.25	1.30	1.40
A2	2.20	2.40	2.60
b	0.70	0.80	0.90
b1	1.42	1.52	1.62
b2	1.17	1.27	1.37
c	0.45	0.50	0.60
D	15.50	15.70	15.90
D1	9.00	9.20	9.40
D2	13.10	13.30	13.50
E	9.70	9.90	10.10
E1	(8.00)		
E2	(0.60)		
E3	9.80	10.00	10.20
e	2.54 BSC		
e1	5.08 BSC		
H1	6.30	6.50	6.70
L	12.88	13.08	13.28
L1	(3.00)		
øP	3.40	3.60	3.80
Q	2.70	2.80	2.90

NOTE

1. THESE DIMENSIONS DO NOT INCLUDE PROTRUSIONS OF THE MOLD.
2. THE "()" MARK IS THE REFERENCE
3. THERMAL PAD (HEAT SINK) CONTOUR OPTIONAL WITHIN SPECIFIED DIMENSIONS.

Important Notice

Elevation reserves the right to modify, improve, and terminate its products, services, documentations, etc. without advance notice. Customers are encouraged to contact Elevation sales representatives to get the latest product information.

Without proper legal authorization, Elevation products shall not be used for medical or military applications. Elevation does not assume any liability of personal or property damages of any kind due to such applications.

All text, images, trademarks of this document, and any intellectual property contained in the product and in this document belong to Elevation. No part of this document may be used, copied, modified, distributed, or published without legal authorization from Elevation.

© 2022 Elevation Microsystems. All rights reserved. www.elevationmicro.com